

Control panel SCP



The control panels are manufactured with an inclined cover and roof overhang. The standard panel cover comes with a gas spring to keep the cover in place.

Standard equipment

- Sheet metal thickness: Cabinet body 1.5 mm / door 2.0 mm
- Material: Made entirely from stainless steel
Material 1.4301 (AISI 304)
- Surface: Polished (grain size 400)
- Hinges: 117° inside hinges
- Locking mechanism: Latch lock with 5 mm double bit insert
- Seal: Silicone profile gasket, 25 x 10, blue
- Right-hand door closure
- Mounting panel: S235 (St37) galvanised
- Protection class: IP 65
- Panel cover with gas springs to keep cover in place
- Housing and doors with earth bolts

Equipment options

- | | | | |
|------------------------|---|---------------------------|-----------|
| Stainless steel: | ■ 1.4571 (AISI 316) | ■ 1.4404 (AISI 316L) | |
| Surface: | ■ Grain-blasted | ■ Grain size 240 polished | ■ Pickled |
| Hinges: | ■ 180° outside latch hinge | | |
| Latch lock mechanisms: | ■ Double bit 3 mm | ■ T-handle | |
| | ■ Triangle 8 mm | ■ Lock handle | |
| | ■ Square 8 mm | ■ Latch handle | |
| Locking mechanism: | ■ Rod-locking mechanism (three-point locking) | | |
| Seal: | ■ Hollow section clamped profile | | |
| Door closing: | ■ left-hand | | |
| Mounting panel: | ■ Stainless steel | | |
| Protection class: | ■ IP 66 | ■ Aluminium | |
| | | ■ IP 69 K | |

Accessory equipment

- | | | |
|-----------------------------|----------------------|--------|
| ■ Water jet protection hood | ■ Drawer mechanism | ■ Base |
| ■ Monitor cover | ■ Door stopper | |
| ■ Surface-mounted door | ■ Cable flange plate | |
| ■ Swivelling frame | | |

Customised features

- | | |
|------------------------|--------------------------------|
| ■ Cut-outs | ■ Sheet metal thickness 2-3 mm |
| ■ Holes | |
| ■ Special requirements | |